

P23568.A17

IN THE CLAIMS

Please amend claims 1, 43-45, 47 and 48 as follows:

1. (Currently Amended) A lancet device, comprising:

a body;

a trigger movably mounted to the body;

a front cover removably mounted to the body and comprising a skin engaging end that includes a lancet opening through which a lancet needle may extend;

a holding member movably mounted within the body and comprising a front end and a rear end;

a main spring disposed inside the body between the front and rear ends of the holding member;

the front end being configured to receive a lancet;

a first stop surface that moves with the holding member and being arranged closer to the front end of the holding member than to the rear end of the holding member;

a second stop surface non-movably coupled to the body; and

the second stop surface extending inwardly from the body and being arranged closer to a front end of the body than to a rear end of the body and between the first stop surface and the skin engaging end,

wherein at least partial rotation of the front cover causes the skin engaging end to move axially relative to the second stop surface, and

wherein contact between the first and second stop surfaces defines a puncturing position of the lancet needle.

2. (Original) The lancet device of claim 1, further comprising a back cap configured to move between a retracted position and an original position.

P23568.A17

3. (Original) The lancet device of claim 2, wherein the back cap is configured to move the holding member to a retracted position.

4. (Withdrawn) The lancet device of claim 2, wherein the back cap is coupled to a surface that engages the rear end of the holding member.

5. (Withdrawn) The lancet device of claim 2, wherein the back cap includes a surface that engages the rear end of the holding member.

6. (Withdrawn) The lancet device of claim 5, wherein the back cap comprises an opening that receives a rear end of the holding member.

7. (Withdrawn) The lancet device of claim 2, wherein the back cap includes a surface that engages projections disposed on the rear end of the holding member.

8. (Original) The lancet device of claim 2, further comprising another spring for biasing the back cap towards an original position.

9. (Original) The lancet device of claim 1, wherein the main spring biases the holding member towards an extended position, and further comprising another spring for biasing the holding member in an opposite direction.

10. (Original) The lancet device of claim 9, wherein said main spring and said other spring are arranged to surround portions of the holding member.

11. (Original) The lancet device of claim 9, wherein the main spring is coupled one side of the holding member and to a surface of the body.

P23568.A17

12. (Original) The lancet device of claim 11, wherein the holding member comprises cylindrical surfaces and a polygonal cross-sectional shape.

13. (Original) The lancet device of claim 11, further comprising a locking member mounted to the rear end of the holding member.

14. (Original) The lancet device of claim 13, wherein the main spring surrounds a portion of the holding member and wherein the other spring is disposed between a surface of a back cap and the locking member.

Claims 15 and 16 (Canceled).

17. (Original) The lancet device of claim 1, further comprising a mechanism for at least temporarily maintaining a depth setting position of the front cover.

18. (Original) The lancet device of claim 1, wherein the holding member comprises an integrally formed deflecting member that engages a surface of the body.

19. (Original) The lancet device of claim 1, wherein the front end comprises an opening that is configured to removably receive the lancet.

20. (Original) The lancet device of claim 1, further comprising a deflecting member configured to be deflected by the trigger.

21. (Original) The lancet device of claim 20, wherein the deflecting member is coupled to the holding member.

22. (Original) The lancet device of claim 20, wherein the deflecting member comprises an engaging surface that contacts a surface of the body.

P23568.A17

23. (Original) The lancet device of claim 22, wherein the deflecting member is integrally formed with the holding member.

24. (Original) The lancet device of claim 1, further comprising indicia arranged on at least one of the front cover and the body.

25. (Original) The lancet device of claim 24, wherein the indicia is arranged on an outer circumferential surface of the body.

26. (Original) The lancet device of claim 24, wherein the indicia is arranged on an outer circumferential surface of the front cover.

27. (Original) The lancet device of claim 1, wherein the holding member comprises a front portion that includes the front end and a rear portion that includes the rear end, wherein the front and rear portions are connected together.

28. (Original) The lancet device of claim 27, wherein the rear portion comprises a locking end which receives a locking member.

29. (Original) The lancet device of claim 28, wherein the front portion comprises a deflecting member configured to be deflected by the trigger.

30. (Original) The lancet device of claim 1, wherein the front cover rotates about an axis that runs through the lancet opening and the holding member.

31. (Original) The lancet device of claim 1, wherein the main spring is disposed between the trigger and a back cap.

32. (Original) The lancet device of claim 1, wherein the body comprises a two-piece body.

P23568.A17

33. (Original) The lancet device of claim 32, further comprising another spring axially retained between walls of the two-piece body.

Claim 34. (Canceled).

35. (Previously Presented) The lancet device of claim 33, further comprising a back cap movably mounted to the two-piece body.

36. (Original) The lancet device of claim 1, wherein the body comprises an ergonomic shape.

37. (Original) The lancet device of claim 1, wherein the body comprises cylindrical surfaces.

38. (Original) The lancet device of claim 1, wherein the body comprises a plastic material.

39. (Original) The lancet device of claim 1, wherein the front cover comprises gripping protrusions.

40. (Original) The lancet device of claim 1, further comprising threads connecting the front cover to the body.

41. (Original) A method of puncturing a surface of skin using the lancet device of claim 1, the method comprising:

adjusting a set depth of penetration of the needle by rotating the front cover to a desired set position;

disposing the skin engaging end of the lancet device against a user's skin; and

triggering the trigger to cause the lancet needle to penetrate the user's skin,

wherein the puncture allows a blood sample to be taken.

P23568.A17

42. (Original) A method of using the lancet device of claim 1, the method comprising:
rotating the front cover to a desired set position;
moving the holding member to a retracted position;
maintaining the holding member in the retracted position until the trigger is triggered;
disposing the skin engaging end of the lancet device against a user's skin; and
triggering the trigger to cause movement of the holding member.

43. (Currently Amended) A lancet device, comprising:
a body;
a front cover comprising a skin engaging end that includes a lancet opening through which a lancet needle may extend;
a holding member movably mounted within the body, the holding member comprising a front end and a rear end;
the front end being configured to receive a lancet;
~~a main spring arranged closer to the front end of the holding member than the rear end and~~
~~being disposed~~ inside the body and between the front and rear ends of the holding member;
a first stop surface arranged on a front portion of the holding member and being disposed inside the body; and
a second stop surface axially retained to a front portion of the body and being disposed inside the body,
wherein at least partial rotation of the front cover causes the skin engaging end to move axially relative to the second stop surface, and
wherein contact between the first and second stop surfaces defines a puncturing position of the lancet needle.

44. (Currently Amended) A lancet device, comprising:
a body;
a trigger;

P23568.A17

a front cover comprising a skin engaging end that includes a lancet opening through which a lancet needle may extend;

a holding member movably mounted within the body, the holding member comprising a front end and a rear end;

the front end being configured to receive a lancet;

a first spring ~~arranged closer to the front end of the holding member than the rear end and~~ being disposed inside the body between the front end of the holding member and a surface of the body;

a back cap configured to move the holding member to a retracted position and having a portion which extends within a rear portion of the body;

a second spring disposed between the rear end of the holding member and a surface of the back cap;

a first stop surface coupled to a front portion of the holding member and being disposed inside the body; and

a second stop surface axially retained to a front portion of the body and being disposed inside the body,

wherein at least partial rotation of the front cover causes the skin engaging end to move axially relative to the second stop surface, and

wherein contact between the first and second stop surfaces defines a puncturing position of the lancet needle.

45. (Currently Amended) A lancet device, comprising:

a body;

a trigger mounted to the body;

~~a trigger spring adapted to bias the trigger towards an initial position;~~

a removable front cover comprising a skin engaging end that includes a lancet opening through which a lancet needle may extend;

P23568.A17

a holding member movably mounted within the body and comprising a rear end and a front end configured to receive a lancet;

a wall arranged within the housing and comprising an opening which allows a portion of the holding member to pass therethrough;

a first spring structured and arranged to move the holding member to an extended position and comprising one end which contacts a portion of the holding member; and

a second spring structured and arranged to move the holding member from the extended position to an intermediate position;

a first stop surface arranged on the holding member and being disposed inside the body at a location that is closer to a front end of the body than to a rear end of the body when the holding member is in the intermediate position; and

a second stop surface arranged inside the body and located closer to the front end of the body than to the rear end of the body,

wherein, when the holding member is positioned in a trigger-set position, the front end is arranged on a front side of the wall and the rear end is arranged on back side of the wall, and

wherein contact between the first and second stop surfaces defines the extended position.

46. (Previously Presented) The lancet device of claim 45, wherein a triggering of the lancet device is caused by movement of the trigger against the biasing force of the trigger spring and by deflection of a deflectable portion of the holding member.

47. (Currently Amended) The lancet device of claim 45, wherein a triggering of the lancet device is caused by the following:

movement of the trigger ~~against the biasing force of the trigger spring~~; and

deflection of a deflectable portion of the holding member from a position wherein a surface of the deflectable portion contacts a portion of the body to a position wherein the surface of the deflectable portion does not contact the portion of the body.

P23568.A17

48. (Currently Amended) The lancet device of claim 45, wherein a triggering of the lancet device is caused by the following:

movement of the trigger ~~against the biasing force of the trigger spring~~ from the initial position to a position wherein a portion of the trigger contacts a deflectable portion of the holding member; and

deflection of the deflectable portion of the holding member from a position wherein a surface of the deflectable portion contacts a portion of the body to a position wherein the surface of the deflectable portion does not contact the portion of the body.